



STORMSHIELD

NETWORK SECURITY

STORMSHIELD SN510

Business continuity in complex architectures



5 Gbps

FIREWALL
PERFORMANCE

1 Gbps

IPSEC
PERFORMANCE

850 Mbps

ANTIVIRUS
PERFORMANCE

12 ports

10/100/1000
INTERFACES



COMMON
CRITERIA



COMMON
CRITERIA



EU
RESTRICTED



NATO
RESTRICTED



Easy and seamless integration

With an emphasis on interoperability and incorporating advanced networking features, Stormshield Network Security product is exceptionally easy to integrate into your existing infrastructure.



Best-of-breed in UTM

- Our partners are recognised and leader in their domain
- Antivirus, Antispam, Web filtering



Compliance with regulations

- Logs and reports access complies with GDPR
- Log storage
- Legal archiving



Keep up with growing mobility while staying safe

- SSL VPN compatible with all operating systems (Android, Apple, Windows, ...)
- Secure connections to internal resources for mobile users

NEXT GENERATION UTM
& FIREWALL

MID-SIZE BUSINESSES
& LARGE BRANCH OFFICES

WWW.STORMSHIELD.COM

TECHNICAL SPECIFICATIONS

PERFORMANCE*

Firewall throughput (1518 byte UDP)	5 Gbps
IPS throughput (1518 byte UDP)	3 Gbps
IPS throughput (1 MByte HTTP files)	1.7 Gbps
Antivirus throughput	850 Mbps

VPN*

IPSec throughput - AES128/SHA1	1 Gbps
IPSec throughput - AES256/SHA2	780 Mbps
Max number of IPSec VPN tunnels	500
Max number of SSL VPN (Portal mode)	75
Number of simultaneous SSL VPN clients	100

NETWORK CONNECTIVITY

Concurrent connections	500,000
New connections per second	20,000
Number of main gateways (max)/backup (max)	64/64

CONNECTIVITY

10/100/1000 Interfaces	12
------------------------	----

SYSTEM

Max number of filtering rules	8,192
Max number of static routes	2,048
Max number of dynamic routes	10,000

REDUNDANCY

High Availability	✓
-------------------	---

HARDWARE

Local storage	320 GB
Log partition	> 300 GB
MTBF at 25°C (years)	14.5
Racking	1U - 19"
Height x Width x Depth (mm)	44.45 x 440 x 310
Weight	4.25 kg (9.4 lbs)
Packaged Height x Width x Depth (mm)	142 x 590 x 443
Packaged weight	6.2 kg (13.7 lbs)
Power supply (AC)	100-240V 60-50Hz 3-1.5A
Power consumption	230V 50Hz 34W 0.21A
Fan	2
Noise level	55dbA
Thermal dissipation (max, BTU/h)	130
Operational temperature	5° to 40°C (41° to 104°F)
Relative humidity, operating (without condensation)	20% to 90% @ 40°C
Storage temperature	-30° to 65°C (-22° to 149°F)
Relative humidity, storage (without condensation)	5% to 95% @ 60°C

CERTIFICATIONS

Compliance	CE/FCC/CB
------------	-----------

FEATURES

USAGE CONTROL

Firewall/IPS/IDS mode - Identity-based firewall - Application detection and management - Microsoft Services Firewall - Industrial firewall/IPS/IDS - Industrial application control - Detection and control of the use of mobile terminals - Application inventory (option) - Vulnerability detection (option) - Geolocation (countries, continents) - Dynamic Host Reputation - URL filtering (embedded database or cloud mode) - Transparent authentication (Active Directory, SSO Agent, SSL, SPNEGO) - Multi-user authentication in cookie mode (Citrix-TSE) - Guest and sponsorship mode authentication.

PROTECTION FROM THREATS

Intrusion detection and prevention - Protocols autodetection and compliancy check - Application inspection - Protection from denial of service attacks (DoS) - Protection from SQL injections - Protection from Cross-Site Scripting (XSS) - Protection from malicious Web2.0 code and scripts (Clean & Pass) - Trojan detection - Detection of interactive connections (botnets, Command&Control) - Protection from data evasion - Advanced management of fragmentation - Automatic reaction to attack (notification, quarantine, block, QoS, dump) - Antispam and antiphishing; reputation-based analysis, heuristic engine - Embedded antivirus (HTTP, SMTP, POP3, FTP) - SSL decryption and inspection - VoIP protection (SIP) - Collaborative security: IP reputation, Cloud based Sandbox on the European territory (option).

CONFIDENTIALITY

Site-to-site or nomad IPSec VPN - Remote SSL VPN access in multi-OS tunnel mode (Windows, Android, iOS, etc.) - SSL VPN agent with automatic configuration (Windows) - Support for Android/iPhone IPSec VPN.

NETWORK - INTEGRATION

IPv6 - NAT, PAT, transparent (bridge)/routed/hybrid modes - Dynamic routing (RIP - OSPF - BGP) - Multiple link management (balancing, failover) - Multi-level internal or external PKI management - Multi-domain authentication (including internal LDAP) - Explicit proxy - Policy-based routing (PBR) - QoS management - DHCP client/relay/server - NTP client - DNS proxy-cache - HTTP proxy-cache - LACP management - Spanning-tree management (RSTP/MSTP).

MANAGEMENT

Web-based management - Interface with privacy mode (GDPR compliancy) - Object-oriented security policy - Contextual security policy - Real-time configuration helper - Rule counter - Multiple installation wizards - Global/local security policy - Embedded log reporting and analysis tools - Interactive and customizable reports - Support for multiple syslog server UDP/TCP/TLS - SNMP v1, v2c, v3 agent - IPFIX/NetFlow - Automated configuration backup - Open API - Script recording.

Non-contractual document. The features mentioned are those in version 3.x.

* Performance is measured in a laboratory and under conditions ideal for version 3.x. Results may vary according to test conditions and the software version.